

<b>MATERIAL SAFETY DATA SHEET</b>
Title: <b>COMPRESSED CARBONIT MATERIAL SAFETY DATA SHEET</b>
Date of Issue: 1 August 2018
Date of Next Review: 1 August 2023

## MATERIAL SAFETY DATA SHEET COMPRESSED CARBONIT®



### IDENTIFICATION:

**Chemical Name:** Carbon Dioxide & Nitrogen  
**Synonyms:** Carbonit 80, Carbonit 60  
**UN Number:** 1956  
**Use:** Inert Atmospheres, used in Beverage Processes.

### HAZARDS IDENTIFICATION:

**Dangerous Goods Class and Subsidiary Risk:** 2.2

**HSNO Classification:** Not Hazardous

**Hazard Statement:**  
 Contains gas under pressure; may explode if heated.

**Precautionary Statements:**  
 Read label before use.  
 Read Safety Data Sheet before use.  
 Protect from sunlight and heat.  
 Store in a well-ventilated place.  
 Wear protective gloves and eye protection.

### COMPOSITION / INGREDIENTS:

Chemical Entity	CAS Number	Proportion
Carbon Dioxide	124-38-9	60 – 80%
Nitrogen	7727-37-9	40 – 20%

Prepared By:	MAM	Document Number:	MSDS 004	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/03/2017	File Location:	MASTER FILE
Reason for Amendment:	UPDATE	Revision Number:	REV 002	Page Number:	1

<b>MATERIAL SAFETY DATA SHEET</b>
Title: <b>COMPRESSED CARBONIT MATERIAL SAFETY DATA SHEET</b>
Date of Issue: 1 August 2018
Date of Next Review: 1 August 2023

Contains no other components or impurities that will influence the classification of the product.

<b>FIRST AID MEASURES:</b>
----------------------------

**Health Effects**

**Acute**

Swallowed: Not applicable to gases.

Eye: Immediately flush eyes thoroughly with water for at least 15 minutes.

Skin: Not irritating to the skin.

**Inhaled:** Carbonit is non-toxic at normal temperature and pressure.

By diluting the oxygen concentration in air below the level necessary to support life, it can act as an asphyxiant.

Effects of oxygen deficiency are:

**16%:** breathing and pulse rate increased, impaired thinking and attention, reduced coordination;

**14%:** Abnormal fatigue upon exertion, emotional upset, faulty coordination, poor judgement;

**12.5%:** Very poor judgement and coordination, impaired respiration that can cause permanent hear damage, nausea and vomiting;

**below 10%:** Inability to perform various movements, loss of consciousness, convulsions, and death.

**The effects of Carbon Dioxide enrichment are:**

**1%:** Slight and unnoticeable increase in breathing rate;

**2%:** Breathing becomes deeper and rate will increase above the normal level. Prolonged exposure for several hours may cause a headache and a feeling of exhaustion;

**3%:** Breathing will start to feel laboured and breathing rate will increase to twice the normal rate. Hearing ability will be reduced; blood pressure and pulse rate will increase. Headaches will also be evident.

**4 – 5%:** Breathing rate will increase to four times the normal rate. Signs of intoxication will be evident after ½ hour exposure and you will have a slight choking feeling in addition to the symptoms above.

Prepared By:	MAM	Document Number:	MSDS 004	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/03/2017	File Location:	MASTER FILE
Reason for Amendment:	UPDATE	Revision Number:	REV 002	Page Number:	2

<b>MATERIAL SAFETY DATA SHEET</b>
Title: <b>COMPRESSED CARBONIT MATERIAL SAFETY DATA SHEET</b>
Date of Issue: 1 August 2018
Date of Next Review: 1 August 2023

**5 – 10%:** Carbon dioxide will have a sharp smell. There will be visual disturbance, laboured breathing, headache, and ringing in the ears. Confusion will be followed by loss of consciousness.

**10 – 100%:** Levels above 10% will lead to rapid loss of consciousness. Further exposure at higher concentrations leads to asphyxiation.

#### **Chronic**

Long term exposure to carbon dioxide has no known health effects. Prolonged exposure to an oxygen deficient atmosphere (below 19% oxygen in air) may affect the heart and nervous system.

#### **First Aid**

##### **Inhalation:**

In high concentrations may cause headaches, nausea and vomiting which may lead to unconsciousness as well as asphyxiation. Symptoms may include loss of mobility/consciousness. Remove victim to uncontaminated area whilst wearing self-contained breathing apparatus.

Victim may not be aware of asphyxiation.

Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

##### **Advice to Doctor**

Advise doctor that victim has been exposed to an oxygen deficient atmosphere.

##### **General:**

Rescuers should not enter an oxygen deficient atmosphere without using self-contained full face positive pressure breathing equipment.

### **FIRE FIGHTING MEASURES:**

##### **Flammability:**

Non Flammable.

##### **Fire/Explosion Hazard:**

Non-flammable, however exposure to fire may cause container to rupture/explode. Cylinders involved in a fire/explosion may rocket. Move cylinders from vicinity of fire if safe to do so.

Cool cylinders by spraying flooding quantities of water from a protected location. If unable to keep cylinders cool, evacuate area, minimum distance 200 meters.

Prepared By:	MAM	Document Number:	MSDS 004	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/03/2017	File Location:	MASTER FILE
Reason for Amendment:	UPDATE	Revision Number:	REV 002	Page Number:	3

<b>MATERIAL SAFETY DATA SHEET</b>
Title: <b>COMPRESSED CARBONIT MATERIAL SAFETY DATA SHEET</b>
Date of Issue: 1 August 2018
Date of Next Review: 1 August 2023

**Extinguishing Media:**

Use appropriate media to extinguish source of surrounding fire. Cool cylinders with water if possible.

**Hazchem Code:** 2 T

<b>ACCIDENTAL RELEASE MEASURES:</b>
-------------------------------------

**Personal Protection:**

Personnel engaged in the movement of cylinders shall be provided with safety footwear, safety glasses and leather or PVC gloves. Full cover overalls are recommended

**Reference Guide:**

Standard SNZ HB 76:2008 Dangerous Goods – Initial Emergency Response Guide.  
AS/NZS 1337 – Eye Protection for Industrial Applications  
AS/NZS 2161.1 – Occupational Protective Gloves – Selection, use and maintenance  
AS/NZS 1715 – Selection, Use and Maintenance of Respiratory Protective Devices  
AS/NZS 1716 – Respiratory Protective Devices

**General:**

Only experienced and properly instructed personnel should handle compressed gases. Cylinder contents and identification labels provided by the supplier must not be removed or defaced. Colour coding should not be the only criterion used for content identification

<b>HANDLING AND STORAGE:</b>
------------------------------

**Handling**

Flammability: Non Flammable.

**General:**

Only experienced and properly instructed personnel should handle compressed gases. Cylinder contents and identification labels provided by the supplier must not be removed or defaced. Colour coding should not be the only criterion used for content identification.

**Approved Handlers:**

Approved handlers are not required, non-hazardous gas (HSNO).

**Storage:**

Storage of compressed gas cylinders shall be in compliance with New Zealand HSNO Regulations.

Cylinders will be kept away from ignition sources (including static discharges).

Prepared By:	MAM	Document Number:	MSDS 004	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/03/2017	File Location:	MASTER FILE
Reason for Amendment:	UPDATE	Revision Number:	REV 002	Page Number:	4

<b>MATERIAL SAFETY DATA SHEET</b>
Title: <b>COMPRESSED CARBONIT MATERIAL SAFETY DATA SHEET</b>
Date of Issue: 1 August 2018
Date of Next Review: 1 August 2023

Cylinders shall be stored in a cool, dry, well-ventilated area out of direct sunlight and away from heat and ignition sources.  
 No part of cylinders shall be exposed to temperatures above 50°C.  
 Cylinders shall be stored upright on a level, fireproof floor, secured in position, and protected from damage.  
 Full cylinders shall be stored separately from empties.  
 Cylinders should be moved by hand-truck or cart designed for that purpose.

**Separation:**

Avoid any contact with oil or grease particularly to the cylinder valve.  
 Carbonit can be stored with most common substances.

<b>EXPOSURE CONTROLS / PERSONAL PROTECTION:</b>
-------------------------------------------------

**Exposure Standards:**

Carbon Dioxide: TWA 5,000 ppm v/v  
 STEL: 30,000 ppm v/v  
 Nitrogen is a simple asphyxiant.

**Engineering Controls:**

Provide adequate local exhaust and dilution via general ventilation and supply sufficient replacement air to maintain oxygen levels above 19%.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature.

Provide adequate local exhaust and dilution (general) ventilation and supply sufficient replacement air to maintain oxygen concentration above 19%.

**Personal Protection:**

Personnel engaged in the movement of cylinders shall be provided with safety footwear, safety glasses and leather or PVC gloves.

Full cover overalls are recommended. In areas where equipment failure may cause an immediate high concentration of Carbonit, ensure adequate ventilation and have approved self-contained, full face respiratory equipment readily available for emergencies.

Equipment employed shall be designed to withstand process pressure and temperature.

**Reference Guide:**

AS/NZS 1337 – Eye Protection for Industrial Applications

Prepared By:	MAM	Document Number:	MSDS 004	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/03/2017	File Location:	MASTER FILE
Reason for Amendment:	UPDATE	Revision Number:	REV 002	Page Number:	5

<b>MATERIAL SAFETY DATA SHEET</b>
Title: <b>COMPRESSED CARBONIT MATERIAL SAFETY DATA SHEET</b>
Date of Issue: 1 August 2018
Date of Next Review: 1 August 2023

AS/NZS 2161.1 – Occupational Protective Gloves – Selection, use and maintenance  
 AS/NZS 1715 – Selection, Use and Maintenance of Respiratory Protective Devices  
 AS/NZS 1716 – Respiratory Protective Devices

<b>PHYSICAL AND CHEMICAL PROPERTIES:</b>
------------------------------------------

**Physical Properties**

Appearance: Colourless, Sharp Odour,  
 Flashpoint: Non Flammable

**Boiling Point:** -78.5°C

**Flammability Limits:** Non Flammable

**Vapour Pressure:** (at 15°C): 5090 kPa

**Solubility in Water (at 0°C):** 1.716 m<sup>3</sup>/kg

**Other Properties**

Relative Density: (Air = 1):1.53  
 Density of Gas: (101.3 kPa, 15°C): 1.873 kg/m<sup>3</sup>  
 Molecular Weight: 44.01  
 Critical Temperature: 31.06°C

<b>STABILITY AND REACTIVITY:</b>
----------------------------------

**Flammability:**

Carbonit is non- flammable.

**Materials Compatibility:** Not applicable.

**Stability:** Stable under normal conditions

<b>TOXICOLOGY INFORMATION:</b>
--------------------------------

In high concentrations, can cause rapid circulatory insufficiency. Symptoms are headache, nausea and vomiting which may lead to unconsciousness.

Prepared By:	MAM	Document Number:	MSDS 004	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/03/2017	File Location:	MASTER FILE
Reason for Amendment:	UPDATE	Revision Number:	REV 002	Page Number:	6

<b>MATERIAL SAFETY DATA SHEET</b>
Title: <b>COMPRESSED CARBONIT MATERIAL SAFETY DATA SHEET</b>
Date of Issue: 1 August 2018
Date of Next Review: 1 August 2023

<b>ECOLOGICAL INFORMATION:</b>
--------------------------------

No known ecological damage caused by this product.  
 When discharged in large quantities, Carbon Dioxide contributes to the greenhouse effect.  
 Global warming factor (CO<sub>2</sub> = 1): 1

<b>DISPOSAL CONSIDERATIONS:</b>
---------------------------------

Do not discharge into any place where its accumulation could be dangerous. To atmosphere in large quantities should be avoided

<b>TRANSPORT INFORMATION:</b>
-------------------------------

**UN Number:** 1956  
**Proper Shipping Name:** COMPRESSED GAS, N.O.S (CARBON DIOXIDE & NITROGEN)  
**Dangerous Goods Class and Subsidiary Risk:** 2.2  
**Packing Group:** Not applicable  
**Hazchem Code:** 2 T

**Other Information:**  
 Avoid transport on vehicles where the load is not separated from the driver's compartment.  
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

**Before transporting product containers:**  
 Ensure that containers are firmly secured.  
 Ensure cylinder valve is closed and not leaking.  
 Ensure there is adequate ventilation.  
 Compliance with applicable regulations.

<b>REGULATORY INFORMATION:</b>
--------------------------------

**Environmental Protection Agency Register Approval No:** HSR002533

**HSNO Controls:**  
 Hazardous Substances (Compressed Gases) Regulations 2004.  
 Hazardous Substances (Tank Wagon and Transportable Containers) Regulations 2004.

Prepared By:	MAM	Document Number:	MSDS 004	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/03/2017	File Location:	MASTER FILE
Reason for Amendment:	UPDATE	Revision Number:	REV 002	Page Number:	7

<b>MATERIAL SAFETY DATA SHEET</b>
Title: <b>COMPRESSED CARBONIT MATERIAL SAFETY DATA SHEET</b>
Date of Issue: 1 August 2018
Date of Next Review: 1 August 2023

**Approved Handlers:** Approved handlers are not required, non-hazardous gas (HSNO).

<b>OTHER INFORMATION:</b>
---------------------------

Compressed Carbonit is supplied in high pressure cylinders.

**Cylinder Colours:**

**Industrial:** AS2700 –Green Grey body (N32) with Pewter coloured shoulders and neck (N63)

**Cylinder Valve Outlet:**

**Industrial:** AS 2473.2 Type 30

**References:**

NZS 5433:2007 Transport of Dangerous Goods on Land  
 EPA Website – Approvals Register – [www.epa.govt.nz](http://www.epa.govt.nz)  
 SNZ HB76:2008 Dangerous Goods – Initial Emergency Response Guide  
 AS1678 2C1 Emergency Procedure Guide – Transport – Non-Flammable, Compressed Gas  
 AS 4484-2004 - Gas Cylinders for Industrial, Scientific, medical and refrigerant use -  
 Labelling and colour coding  
 AS 2473.2-2007 - Valves for compressed gas outlets - Part 2 Outlet connections (threaded) and stem (inlet) threads  
 AS 2473.3-2007 - Valves for compressed gas outlets - Part 3 Outlet connections for medical gases (including pin-indexed yoke connections)  
 Operators Handbook for the Transport of Dangerous Goods by Road – NZ Road Transport & Logistics Industry Training Organisation  
 NZCIC Code of Practice – Preparation of Safety Data Sheets

Prepared By:	MAM	Document Number:	MSDS 004	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/03/2017	File Location:	MASTER FILE
Reason for Amendment:	UPDATE	Revision Number:	REV 002	Page Number:	8



<b>MATERIAL SAFETY DATA SHEET</b>
Title: <b>COMPRESSED CARBONIT MATERIAL SAFETY DATA SHEET</b>
Date of Issue: 1 August 2018
Date of Next Review: 1 August 2023

<b>MSDS SUMMARY:</b>
----------------------

This MSDS summarises to our best knowledge, at the date of issue, the health and safety hazard information regarding this product and general guidance on how to safely handle the product in the workplace. All due care has been taken to include accurate and up-to-date information in this MSDS.

Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Southern Gas Services Limited.

As far as lawfully possible, no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS can be accepted.

Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is available on request.

This MSDS has been prepared in accordance with NZCIC Code of Practice – Preparation of Safety Data Sheets.

This MSDS is subject to change without notice.

Prepared By:	MAM	Document Number:	MSDS 004	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/03/2017	File Location:	MASTER FILE
Reason for Amendment:	UPDATE	Revision Number:	REV 002	Page Number:	9