

MATERIAL SAFETY DATA SHEET	
Title: LIQUEFIED R507A MATERIAL SAFETY DATA SHEET	
Date of Issue: 1 August 2019	
Date of Next Review: 1 August 2024	

**MATERIAL SAFETY DATA SHEET
LIQUEFIED GAS NOT OTHERWISE SPECIFIED –
R507A**



SUPPLIER IDENTIFICATION:

New Zealand Supplier: Southern Gas Services Limited
Address: 1/26 Railway Road, Izone Southern Business Hub, Rolleston, New Zealand
Phone Number: (03) 3472691
Emergency Contacts: (03) 3472691 and **0800 766 764 (National Poison Centre)**

Manufacturer: Kaltech Engineering & Refrigeration Pte Ltd
 9 Tuas Link, 1, Singapore

Date of MSDS Preparation: 1 August 2019
Date of Next Review: 1 August 2023

PRODUCT IDENTIFICATION:

Chemical Name: Liquefied Gas, Not Otherwise Specified
Synonyms: R507A
UN Number: 3163
Use: Refrigerant Gas

HAZARDS IDENTIFICATION:

Dangerous Goods Class and Subsidiary Risk: 2.2
HSNO Classification: Not Hazardous

Prepared By:	MAM	Document Number:	MSDS 0034	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/08/2019	File Location:	MASTER FILE
Reason for Amendment:	NEW	Revision Number:		Page Number:	1

MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED R507A MATERIAL SAFETY DATA SHEET
Date of Issue: 1 August 2019
Date of Next Review: 1 August 2024

Hazard Statement:

Contains liquid under pressure; may explode if heated.

Precautionary Statements:

- Read label before use.
- Read Safety Data Sheet before use.
- Protect from sunlight and heat.
- Store in a well-ventilated place.
- Wear protective gloves and eye protection.

COMPOSITION / INGREDIENTS:

Chemical Entity	CAS Number	Proportion
1,1,1,2- Tetrafluoroethane (R134A)	811-97-2	50%
Pentafluoroethane (R125)	354-33-6	50%

Contains no other components or impurities that will influence the classification of the product.

FIRST AID MEASURES:

Health Effects

Swallowed: Ingestion is extremely unlikely because of the low boiling point of the material. Should it occur, discomfort in the gastrointestinal track from rapid evaporation of the material and consequent evolution of gas would result. Some effects of inhalation and skin exposure would be expected.

Eye: Liquid contact can cause severe irritation and frostbite. Mist may also irritate

Skin: Not irritating to the skin. Irritation would result from a defatting action on tissue. Liquid contact can cause frostbite.

Inhaled:R507A is low in acute toxicity in animals. When oxygen levels in air are reduced to 12 – 14% by displacement, symptoms of asphyxiation, loss of co-ordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia can occur.

First Aid

Inhalation: In high concentrations may cause headache, nausea and vomiting, which may lead to unconsciousness as well as asphyxiation. Immediately move to fresh air. If breathing has stopped, give artificial respiration. Use Oxygen as required, provided a qualified operator is available. Get medical attention immediately. DO NOT give epinephrine (Adrenaline)

Prepared By:	MAM	Document Number:	MSDS 0034	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/08/2019	File Location:	MASTER FILE
Reason for Amendment:	NEW	Revision Number:		Page Number:	2

MATERIAL SAFETY DATA SHEET	
Title:	LIQUEFIED R507A MATERIAL SAFETY DATA SHEET
Date of Issue:	1 August 2019
Date of Next Review:	1 August 2024

Skin: Promptly flush skin with water until the entire chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm water (not hot) If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

Eyes: Immediately flush eyes with large volumes of water for at least 15 minutes. In case of frost bite, water should be lukewarm (not hot) lifting eyelids occasionally to facilitate irrigation.

Ingestion: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

Advise to Physician

Because of the possible disturbances of cardiac rhythm, catecholamine drugs such as epinephrine should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and clinic conditions.

FIRE FIGHTING MEASURES:

Flammability:

Non Flammable.

Fire/Explosion Hazard:

R507A is non-flammable at ambient temperatures and atmospheric conditions. However this material will become combustible when mixed with air under pressure and exposed to strong ignition sources. Contact with certain reactive metals may result in formation of explosive or exothermic reactions under special conditions (e.g. very high temperatures and /or appropriate pressures.) Thermal decomposition will evolve very toxic and corrosive vapours.

Extinguishing Media:

Use appropriate media (all known extinguishers can be used) to extinguish source of surrounding fire. Cool cylinders with water if possible.

Hazchem Code: 2 TE

Recommended Protective Clothing: Fire fighters should wear self-contained approved Breathing apparatus for protection against possible toxic decomposition products. Proper eye and skin protection should be worn at all times.

Prepared By:	MAM	Document Number:	MSDS 0034	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/08/2019	File Location:	MASTER FILE
Reason for Amendment:	NEW	Revision Number:		Page Number:	3

MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED R507A MATERIAL SAFETY DATA SHEET
Date of Issue: 1 August 2019
Date of Next Review: 1 August 2024

ACCIDENTIAL RELEASE MEASURES:

Personal Protection:

Personnel engaged in the movement of cylinders shall be provided with safety footwear, safety glasses and leather or PVC gloves. Full cover overalls are recommended. In areas where equipment failure may cause an immediate high concentration of R507A, ensure adequate ventilation and have approved self-contained, full face respiratory equipment readily available for emergencies.

Spills and Disposal:

Evacuate unprotected personnel. Product dissipates upon release. Protected personnel should remove ignition sources and shut off leak, if without risk and provide ventilation. Unprotected persons should not return to the affected area until the air has been tested and determined safe, including low lying areas.

Reference Guide:

Standard SNZ HB 76:2008 Dangerous Goods – Initial Emergency Response Guide.
 AS/NZS 1337 – Eye Protection for Industrial Applications
 AS/NZS 2161.1 – Occupational Protective Gloves – Selection, use and maintenance
 AS/NZS 1715 – Selection, Use and Maintenance of Respiratory Protective Devices
 AS/NZS 1716 – Respiratory Protective Devices

General:

Only experienced and properly instructed personnel should handle compressed and liquefied gases. Cylinder contents and identification labels provided by the supplier must not be removed or defaced. Colour coding should not be the only criterion used for content identification.

HANDLING AND STORAGE:

Handling

Flammability: Non Flammable.

General:

Only experienced and properly instructed personnel should handle compressed or liquefied gases. Cylinder contents and identification labels provided by the supplier must not be removed or defaced. Colour coding should not be the only criterion used for content identification. Always wear PPE. Avoid breathing vapours and liquid contact with eyes, skin and clothing. Do not puncture or drop cylinders, expose them to open flame or excessive heat.

Prepared By:	MAM	Document Number:	MSDS 0034	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/08/2019	File Location:	MASTER FILE
Reason for Amendment:	NEW	Revision Number:		Page Number:	4

MATERIAL SAFETY DATA SHEET	
Title: LIQUEFIED R507A MATERIAL SAFETY DATA SHEET	
Date of Issue: 1 August 2019	
Date of Next Review: 1 August 2024	

R507A should not be mixed with air above atmospheric pressure for leak testing or any other purpose.

Approved Handlers:

Approved handlers are not required, non-hazardous gas (HSNO).

Storage:

Storage of compressed & liquefied gas cylinders shall be in compliance with New Zealand HSNO Regulations.

Cylinders will be kept away from ignition sources (including static discharges).

Cylinders shall be stored in a cool, dry, well-ventilated area out of direct sunlight and away from heat and ignition sources.

Suck-back of water into the cylinder must be prevented.

No part of cylinders shall be exposed to temperatures above 50°C.

Cylinders shall be stored upright on a level, fireproof floor, secured in position, and protected from damage.

Full cylinders shall be stored separately from empties.

Cylinders should be moved by hand-truck or cart designed for that purpose.

EXPOSURE CONTROLS / PERSONAL PROTECTION:

Exposure Standards:

SUBSTANCE	CAS #	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
1.1.1.2 – Tetrafluoroethane (r134a)	811-97-2	1000	-	-	-
Pentafluoroethane (R125)	354-33-6	1000	-	-	-

Engineering Controls:

Provide adequate local exhaust and dilution (general) ventilation and supply sufficient replacement air to maintain oxygen concentration above 18%.

Personal Protection:

Skin contact: may cause frost bite. If prolonged exposure to liquid or gas is anticipated, insulated gloves constructed of PVA, neoprene or butyl rubber should be used. Any contaminated clothing should be promptly removed and washed.

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles and or a face shield.

Prepared By:	MAM	Document Number:	MSDS 0034	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/08/2019	File Location:	MASTER FILE
Reason for Amendment:	NEW	Revision Number:		Page Number:	5

MATERIAL SAFETY DATA SHEET	
Title: LIQUEFIED R507A MATERIAL SAFETY DATA SHEET	
Date of Issue: 1 August 2019	
Date of Next Review: 1 August 2024	

Additional Recommendations:

Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn. High dose level warning signs are recommended for areas of principle exposure. Provide eye wash stations and quick drench shower facilities at convenient locations.

Reference Guide:

AS/NZS 1337 – Eye Protection for Industrial Applications
 AS/NZS 2161.1 – Occupational Protective Gloves – Selection, use and maintenance
 AS/NZS 1715 – Selection, Use and Maintenance of Respiratory Protective Devices
 AS/NZS 1716 – Respiratory Protective Devices

PHYSICAL AND CHEMICAL PROPERTIES:

Physical Properties:

Appearance: Clear Colourless liquid and gas
Odour: Ethereal and faint sweetish odour.
Boiling Point: -47.2°C – 46.4 °C
Melting Point: 160 °C
Vapour Pressure (20 °C): 1061 Kpa
Vapour density (Air = 1): > 3.43 at bubble point air = 1
Specific Gravity: 1.21
Liquid Density: 11.924 kg/m³
Solubility in water: Insoluble

Other data: Gas/Vapours are heavier than air. May accumulate in confined spaces, particularly at or below ground levels.

STABILITY AND REACTIVITY:

Flammability: Non-flammable.
Normally Stable (Conditions to Avoid): Do not mix with Oxygen or Air above atmospheric pressure. Any source of high temperature such as lighted cigarettes, flames, hot spots or welding may yield toxic and /or corrosive decomposition products. May react with Alkali metals, Sodium, Potassium, Barium, Magnesium, alloys and powdered metals.

Hazardous Decomposition Products: on combustion or thermal decomposition (Pyrolysis) and Hydrolysis releases toxic gases (halogenated compounds) (Hydrogen Chloride and Hydrogen Fluoride)

Prepared By:	MAM	Document Number:	MSDS 0034	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/08/2019	File Location:	MASTER FILE
Reason for Amendment:	NEW	Revision Number:		Page Number:	6

MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED R507A MATERIAL SAFETY DATA SHEET
Date of Issue: 1 August 2019
Date of Next Review: 1 August 2024

TOXICOLOGY INFORMATION:

In high concentrations causes rapid circulatory insufficiency and Cardiac Sensitization. . Symptoms are headache, nausea and vomiting, which may lead to unconsciousness. Acute effects of rapid evaporation of the liquid may cause frostbite. Vapors are heavier than air and can displace oxygen causing difficulties breathing and or suffocation.

ECOLOGICAL INFORMATION:

Behaviour in environment

High tonnage material produces in wholly contained systems.
High tonnage material used in open system

Mobility

Product is volatile in aqueous solutions

Persistence/Degradability

Decomposes comparatively rapidly in lower atmosphere (troposphere), products of decomposition will be highly dispersed and hence have a very low concentration.

Bioaccumulation

Non Bioaccumlable

Destination of Product

Air

DISPOSAL CONSIDERATIONS:

Do not discharge into any place where its accumulation could be dangerous. Dispatch to atmosphere should be avoided. Disposal procedures should comply with relevant discharge regulations. Return to manufacturer/distributor for correct disposal.

TRANSPORT INFORMATION:

UN Number: 3163

Proper Shipping Name: Liquefied Gas, Not Otherwise Specified (R507A)

Dangerous Goods Class and Subsidiary Risk: 2.2

Packing Group: Not applicable

Prepared By:	MAM	Document Number:	MSDS 0034	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/08/2019	File Location:	MASTER FILE
Reason for Amendment:	NEW	Revision Number:		Page Number:	7

MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED R507A MATERIAL SAFETY DATA SHEET
Date of Issue: 1 August 2019
Date of Next Review: 1 August 2024

Hazchem Code: 2TE

Other Information:

Avoid transport on vehicles where the load is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

Ensure that containers are firmly secured.
 Ensure cylinder valve is closed and not leaking.
 Ensure there is adequate ventilation.
 Compliance with applicable regulations.

REGULATORY INFORMATION:

This substance is not hazardous according to the HSNO (Minimum Degree of Hazard) Regulations 2001

OTHER INFORMATION:

R507A is supplied in disposable gas cylinders.

References:

NZS 5433:2007 Transport of Dangerous Goods on Land
 EPA Website – Approvals Register – www.epa.govt.nz
 SNZ HB76:2008 Dangerous Goods – Initial Emergency Response Guide
 AS1678 2C1 Emergency Procedure Guide – Transport – Non-Flammable, Compressed Gas
 Operators Handbook for the Transport of Dangerous Goods by Road – NZ Road Transport & Logistics Industry Training Organisation
 NZCIC Code of Practice – Preparation of Safety Data Sheets

MSDS SUMMARY:

This MSDS summarises to our best knowledge, at the date of issue, the health and safety hazard information regarding this product and general guidance on how to safely handle the product in the workplace. All due care has been taken to include accurate and up-to-date information in this MSDS.

Prepared By:	MAM	Document Number:	MSDS 0034	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/08/2019	File Location:	MASTER FILE
Reason for Amendment:	NEW	Revision Number:		Page Number:	8



MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED R507A MATERIAL SAFETY DATA SHEET
Date of Issue: 1 August 2019
Date of Next Review: 1 August 2024

Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Southern Gas Services Limited.

As far as lawfully possible, no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS can be accepted.

Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is available on request.

This MSDS has been prepared in accordance with NZCIC Code of Practice – Preparation of Safety Data Sheets.

This MSDS is subject to change without notice.

Prepared By:	MAM	Document Number:	MSDS 0034	Number of Copies	1
Authorised By:	WJM	Issue Date:	01/08/2019	File Location:	MASTER FILE
Reason for Amendment:	NEW	Revision Number:		Page Number:	9